C5

DIAPHRAGM PUMP FOR LIQUID APPLICATION



Attributes

100% Oil-free
Excellent gas sealing / Contamination free
Low power consumption and noise level
Quick and easy maintenance procedure
Exceptional motor lifetime
Pump Re-Start at maximum levels
Compact and easy to use

Applications

Aspiration (surgical, welding)
Small portable equipment
Reprographics / Printing
Environmental sampling
Laboratory analysis
Dosing

Performance Data

Maximum Flow (gas)	2.5 l/min
Maximum Flow (liquid)	600 ml/min
Maximum Vacuum (gas)	-500 mbar
Maximum Pressure (gas)	600 mbar
Maximum Pressure (liquid)	18 mH_2O
Maximum pressure Start up	-500 mbar
Maximum pressure Start up	600 mbar

Motor Data

Motor Type	AC shaded pole	
Voltage	230 Vac 50 Hz	120 Vac 60 Hz
Maximum current (gas)	0.45 A	0.90 A
IP	10	
Insulation Class	B (120°C Th. Protection)	
Electrical Connection	Plug power cord length 1.75 m (L+N)	

Dimensions in mm



Additional Data

Average Noise	56 dB
Weight	1300 g

Available Material Options

Head	PPS (alternatives on request)
Diaphragm	FKM (alternatives on request)
Valve	FKM (alternatives on request)
O-Ring	VMQ (alternatives on request)

Service kits

RUBBER KIT H/S5 M/SR L	900.21

Pressure / Flow characteristic (liquid) [1]



[1] Characteristics shown for frequency (f) at 50Hz. If needed info at 60Hz please contact us.

www.electroad.es

HEADQUARTERS
Castellví de Rosanes factories 1 & 2
La Pedrosa Industrial Park
08783 Masquefa; Barcelona; Spain
Tel: +34 937 728 529
Fax: +35 937 728 591
Email: comercial@electroad.es

ITALY SALES OFFICE
Via Giacomo Manzù 25
24122 Bergamo; Italy
Tel: +39 389 445 8471
Tel: +39 320 225 0058
Email: fdonado@ead-pumps.com
Email: sdeleonardis@ead-pumps.com

Your **success** is our satisfaction

Solutions for a **smart world**

Electro A.D., S.L. as a manufacturer does not guarantee or assume any obligation related to the data contained on this document and remarks that it could slightly differ between different products.
Electro A.D., S.L. keeps the right to modify any part or group of parts manufactured without notice in order to improve the product.
C5 Liquid Datasheet rev.0 – All rights reserved.